

JZDRA-92: DRYING RACK



CONSTRUCTION/MATERIAL:

- · Sturdy construction specifically designed for the demanding corrections environment
- All welded construction
- All fasteners are tamper-proof

JZDR (Stainless Steel)

- 14-guage 304 stainless steel construction JZDRA (Aluminum)
- Type 6063-T5 aluminum alloy with wall thickness of 0.070".

WARRANTY:

- Stainless steel: 1-year warranty against manufacturing defect
- Aluminum: 5-year warranty against manufacturing defect

DIMENSIONS/CAPACITY:

Width: 80.50" Height: 72.63" Depth: 22.88"

CAPACITY:

Insulated Tray	
PRTS-5000	
15x11x2	184
PRTS-4000/1	
15x13x2.5	184*
PRTS-6000	
15x14x2.875	184*

Segregation tray	
Large	184
Med & Small	276
Self-stacking tray	
SmartTray	184
•	

COMPONENTS:

Shelves

- Four shelves
- Eight inserts per shelf, thirty-two inserts per rack
- Interchangeable inserts -- mix and match

Casters

Four 6" poly swivel casters with brakes

INSERTS

- Inserts made of copolymer material:
 - Dishwasher safe, temps up to 212°
 - Shatterproof and resists sharpening

JZDRI-3

- Larger, fewer slots, 3" spacing
- 23 slots per shelf, 92 per rack



Run inserts through dishwasher for better sanitation and restore to 'like new'

Plastic inserts prolong life of plastic trays instead of scraping over all metal drying racks

www.joneszylon.com

^{*} with 2" overhang