

JZDRA-156/92: UNIVERSAL DRYING RACK



CONSTRUCTION/MATERIAL:

- Sturdy construction specifically designed for the demanding corrections environment
- All fasteners are tamper-proof
- Type 6063-T5 aluminum alloy with wall thickness of 0.070".

COMPONENTS:

Shelves

- Four shelves
- Eight inserts per shelf, thirty-two inserts per rack
- Interchangeable inserts -- mix and match

Casters

Four 6" poly swivel casters with brakes

WARRANTY:

5-year warranty against manufacturing defect

DIMENSIONS/CAPACITY:

Height: 72.63" Width: 80.50" Depth: 22.88"

CAPACITY:

	Rack capacity per insert		
Item to dry	JZDRI-3	JZDRI-4	JZDRI-5
Sm & Med Seg Trays	276		
Sm/Med Seg tray lids	276	660	468
Large Seg Trays	184		
Large Seg tray lids	184	440	312
PRTS-6000/4000 Insulated Trays	184*		
PRTS-5000 Insulated tray	184		
PPST-28/14 cafeteria tray			312
PPSTL-28 lid			312
PPST-1570 base tray			312
4" Hotel pans (12x20x4)			57
PPST-67 main line tray	Use JDZRA-220-SP rack with JZDRI-5 insert		
Sheet pans	Use JDZRA-220-SP rack with JZDRI-4 insert		

^{*} with 2" overhang

INSERTS – copolymer material

- Dishwasher safe, temps up to 212°
- Shatterproof and resists sharpening

JZDRI-3

- 3" slots (for seg & insulated trays)
- 23 slots per shelf, 92 per rack

JZDRI-4

- 1.125" slots (for lids, sheet pans)
- 55 slots per shelf, 220 per rack

JZDRI-5

- 1.813" slots (for cafeteria trays)
- 39 slots per shelf, 156 per rack







OWNED www.joneszylon.com