

# JZH-144HD-2RH: HEATED CART

WITH SIDE MOUNT REMOVABLE HEATERS



### DIMENSIONS/CAPACITY:

Height: 66.00"    Width: 62.25"    Depth: 31.75"

### CAPACITY:

	6 shelves	No shelf
9000 Series Trays	228	264
5000 or 4000 Series Trays	310	360

### COMPONENTS:

#### Doors

- Double-panel doors with door-mount gaskets
- Three heavy-duty 12-gauge stainless steel hinges with stitch weld reinforcement
- 12-gauge lockable stainless steel transport latch
- Magnetic door closure

#### Racks

- Optional universal slides for sheet pans and steam pans set at 4 ½" spacing. Custom spacing

#### Display

- Recessed thermometer with security cover

#### Insulation

- Fully insulated top, bottom, and sides with 1" thick high-density fiberglass
- Insulated center wall to divide left and right

#### Handles

- Side-mount recessed push handles on both sides

#### Top rail

- Three-sided welded stainless steel top rail

#### Casters

- Six 8" plate-mounted casters with tamper-proof fasteners
- Multi-terrain (4 swivel with brakes, 2 rigid)

#### Bumpers

- Full perimeter non-marking vinyl bottom bumper reinforced with carriage bolts
- Top corner bumpers

### CONSTRUCTION/MATERIAL:

- All exterior surfaces 18-gauge stainless steel
- Cart reinforced with stainless steel plate at all corners and fittings
- Base frame made of 16-gauge stainless steel with reinforced cross channels
- All fasteners are security type
- All welds are ground and polished

### HEATING/REFRIGERATION/ELECTRICAL:

- Side-mount snap-in removable heating assembly on both sides
- 120 volts / 2400 watts / 20 Amps
- NEMAplug 5-20P
- Stainless steel strain relief on electrical cord. 12-gage cord wrap on heat box
- Each side separately heated with insulated center wall

### WARRANTY AND OPTIONS:

- 1-year parts and labor warranty
- Uptime kit available