

JZHR-144: HEATED/REFRIGERATED CART



DIMENSIONS/CAPACITY:

Height: 76.00" Width: 62.25" Depth: 31.75"
 (63 1/2" cabinet + 12 1/2" compressor)

CAPACITY per side:

			Pans	
<i>Seg Trays w/shelves</i>	<i>No shelf</i>		18" x 26" Sheet Pans	10
9000 Series Trays	72	132	12" x 20" x 4" Pans	20
5000 or 4000 Series Trays	96	180		

CONSTRUCTION/MATERIAL:

- All exterior surfaces made of 18-gauge stainless steel
- Cart reinforced with stainless steel plate at all corners and fittings
- Base frame made of 16-gauge stainless steel with reinforced cross channels
- All fasteners are security type
- All welds are ground and polished

HEATING/REFRIGERATION/ELECTRICAL:

- Bottom-mounted heating system and top-mounted refrigeration system
- 1680 Watts, 14 Amps, 120 Volts
- NEMAPlug: 5-20P
- 12-gauge stainless steel cord wrap welded to cabinet

WARRANTY AND OPTIONS:

- 1-year parts and labor warranty
- Uptime kit available
- Heavy Duty upgrade package available

COMPONENTS:

Doors

- Double-panel doors with door-mount gaskets
- Three heavy-duty 12-gauge stainless steel hinges
- Doors open 270°
- 12-gauge lockable stainless steel transport latch
- Magnetic door closure

Racks

- Universal slides for sheet pans and steam pans set at 4 1/2" spacing. Custom spacing available.

Display

- Recessed digital temperature controller / thermometer with security cover
- Lighted on/off rocker switch w/ sliding cover

Insulation

- Fully insulated top, bottom, and sides with 1" thick high-density fiberglass

Handles

- Side-mount recessed push handles on both sides

Top rail

- Two-sided welded stainless steel top rail

Casters

- Six 8" plate-mounted casters with tamper-proof fasteners
- Multi-terrain (4 swivel with brakes, 2 rigid)

Bumpers

- Full perimeter non-marking vinyl bottom bumper

