

JZR-168: REFRIGERATED CART



CONSTRUCTION/MATERIAL:

- 18-gauge 300 series stainless steel exterior and 20-gauge interior
- Base frame made of 16-gauge stainless steel with reinforced cross channels
- All fasteners are security type
- All welds are ground and polished

REFRIGERATION/ELECTRICAL:

- Top-mounted refrigeration right side
- 120 volts / 817 watts / 6.8 Amps
- NEMA plug 5-15P
- Stainless steel strain relief on electrical cord. 12-gage cord wrap on cart

WARRANTY AND UPTIME KIT:

- 1-year parts and labor warranty
- Uptime kit available

DIMENSIONS/CAPACITY:

Height: 62" Width: 61" Depth: 32.5"

CAPACITY – both sides:

Segregation trays	
9000 series	168
5000 series	280
4000 series	315

Bulk food	
18x26 sheet pans	14
12x20 hotel pans	28

Insulated trays	
PRTS-6000	84
PRTS-5000	112
PRTS-4000	84

Non-insul stacking	
JZ Smart tray	180
Rock	160
X-tray	112
PST-28 (w/ lid)	91

COMPONENTS:

- Doors**
- Magnetic closure double door, door gasket
 - Three heavy-duty 12-gauge stainless steel hinges
 - Drop down padlocking door latch
- Display**
- Solar-powered digital thermometer
- Insulation**
- Fully insulated in top, bottom, and sides with 1" thick high-density fiberglass
- Racks**
- Removable universal racks for 4" steam pans or 18x26 sheet pans at 4 1/2" spacing (optional)
- Handles**
- Push/pull handle on each side
 - Tubular top rail. Sized to fit 2+ milk crates
- Casters**
- Six 6" casters mounted to 1/4" plates
 - Multi-terrain quiet ride (4 swivel w/ brake, 2 rigid)
 - Turns on its own radius on center casters
- Bumpers**
- Full perimeter non-marking vinyl bottom bumper
- Heavy Duty Corrections package**
- Welded hinges, welded corners
 - Lag bolts to retain nylon bumper from pulling out