

JZR-168XL: REFRIGERATED CART



CONSTRUCTION/MATERIAL:

- 18-gauge 300 series stainless steel exterior and 20-gauge interior
- Base frame made of 16-gauge stainless steel with reinforced cross channels
- All fasteners are security type
- All welds are ground and polished

REFRIGERATION/ELECTRICAL:

- Top-mounted refrigeration right side
- 120 volts / 817 watts / 6.8 Amps
- NEMA plug 5-15P
- Stainless steel strain relief on electrical cord. 12-gage cord wrap on cart

WARRANTY AND UPTIME KIT:

- 1-year parts and labor warranty
- Uptime kit available

DIMENSIONS/CAPACITY:

Height: 62" Width: 62.9" Depth: 32.5"

CAPACITY – both sides:

Segregation trays		Bulk food	
9000 series	168	18x26 sheet pan	14
5000 series	294	12x20x4" pans	28
4000 series	368		
Insulated trays		Non-insul stacking	
PRTS-6000	52	JZ Smart tray	170
PRTS-5000	112	Rock	160
PRTS-4000	84	X-tray	112
		PPST-28 (w/ lid)	96

COMPONENTS:

Doors

- Magnetic closure double door, door gasket
- Three heavy-duty 12-gauge stainless steel hinges
- Drop down padlocking door latch

Display

- Solar-powered digital thermometer

Insulation

- Fully insulated in top, bottom, and sides with 1" thick high-density fiberglass

Racks

- Removable universal racks for 4" steam pans or 18x26 sheet pans at 4 ½" spacing (optional)

Handles

- Push/pull handle on each side
- Tubular top rail. Sized to fit 2+ milk crates

Casters

- Six 6" casters mounted to ¼" plates
- Premium multi-terrain (4 swivel w/ brake, 2 rigid)
- Turns on its own radius on center casters

Bumpers

- Full perimeter non-marking vinyl bottom bumper

Heavy Duty Corrections package

- Welded hinges, welded corners
- Lag bolts to retain nylon bumper from pulling out